10/222 12. 12 E A4 ® TÜV, TUEV and TUV are registered trademarks. Utilisation and application requires prior approval.

Certificate



968/TA 1645.00/21

Product tested Slide Gate Valves DN 50 - DN 400 Certi

Clean Air Guideline (TA Luft)

Certificate holder

Emil Kammerer GmbH Mülheimer Str. 85

51469 Bergisch Gladbach

Germany

Type designation O-ring (Viton) sealed shifting shaft implementation and housing seal

Codes and standards TA Luft:2002 VDI 2440:2000

Intended application Shaft diameter: 18 mm / 24 mm and 28 mm

Nominal width: DN 50 to DN 400 Temperature range: -15 °C to +150 °C

Pressure range: max. 6 bar Max. shaft movements: 5.000

Specific requirements The instructions of the associated Installation, Operating Manual shall be

considered.

Quality of sealing materials according to order specifications Dimensions, profile and position tolerances according to drawings

Surface roughness according to drawings

Annual production control

Herby it is certified that the manufacturer's sealing system complies with the requirements of the Clean Air Guideline, paragraph 5.2.6.4 in combination with VDI 2440, section 3.3.1.3.

Valid until 2026-07-27

The issue of this certificate is based upon an examination, whose results are documented in Report No. 968/TA 1645.00/21 dated 2021-07-06.

This certificate is valid only for products which are identical with the product tested.

TÜV Rheinland Industrie Service GmbH Bereich Automation

Funktionale Sicherheit

Köln, 2021-07-27 TÜV Rheinland Industrie Service GmbH

Dipl.-Ing. (FH) Wolf Rückwart

TÜV Rheinland Industrie Service GmbH, Am Grauen Stein, 51105 Köln / Germany Tel: +49 221 806-1790, Fax: +49 221 806-1539, E-Mail: industrie-service@de.tuv.com

